



**Network Connection Concession
For Sungard DS2000
Version B12.19X Issue 3
(excluding use of Interim Alias Service)**

The following equipment has been tested for connection to the Airwave network (the "Equipment"). The Equipment has been tested on the Airwave Reference System Rugby.

	Manufacturer/Customer:	Versions:	Other relevant details:	Date(s) Certificate issued:
Supplier and Equipment Information	Sungard Public Sector Marshfield, Chippenham, Wiltshire SN14 8SR	Product Designation:- DS2000 19X Generic See table below for components used with the 3 valid build versions.	Test Date: 21 Sept 10 Document Inspection	Issued: 21 Sept 10 Document Inspection

Build Version	Short Data	CADI	CCI
12.192.3.3	12.192.3.3	12.192.3.3	12.192.2.0
12.192.5.0	12.192.5.0	12.192.5.0	12.192.2.0
12.193.3.1	12.193.3.1	12.193.3.1	12.193.0.0

At the time the Equipment was tested the Airwave Network Reference System was configured as follows:

Airwave interface Software version Centracom Q303	Airwave System was built to baseline R6.2 SSR SPU
--	---

The testing conducted on the Equipment suggests that it will not adversely impact the Airwave Network (as it had been configured in accordance with the above specifications). The testing was limited to terminal conformance in accordance with the latest specification and hence no specific data application functionality or performance of the product was exercised unless specified below or in the test results.

Notes/Observations:

1. This concession certificate is issued following a document inspection only.

Date : 21st September 2010

2. This certificate is not valid for use on the Department of Health Ambulance Radio Project.
3. This certificate does not cover the PEI RIF component which is covered by a separate individual certificate.
4. This certificate does not permit the use of the Interim Aliasing Solution (AIS) functionality. Although included in the software package submitted for test, it only implements a small subset of the available commands. In its present form it is not possible to create RUI and Pin records on the Alias Server. A pin can be changed once a radio user has logged on. However, prior to log-on the record is not visible to the operator. This means that should a radio user lock out his account by using the wrong RUI/PIN combination it is not possible for the operator to remotely log the user on, thus resetting the locked out account. As this is fundamental to the correct operation of the facility.

Disclaimer:

1. This conformance certificate does not indicate any security approval with respects to the operation of this hardware / software on the Airwave network.

It is the responsibility of the supplier and their customer (whether Airwave Solutions Ltd or 3rd party customer) to ensure the Airwave Accreditor's security requirements have been met before this hardware / software is deployed on the Airwave operational network. If this solution is deployed within the customer's security domain then the customers Accreditor / Senior officer responsible for security must give their approval inline with the Airwave Service Code of Connection.

2. The issuing of this Connection Certificate is for information purposes only and Airwave makes no warranty or guarantee whatsoever as to the fitness for purpose of the Equipment or its ability to operate correctly when connected to the Airwave Network or any other network or equipment. Your use of the Equipment, connection of the Equipment to the Airwave Network and reliance on the contents of this Connection Certificate (for whatever purpose) is at your sole risk. Airwave shall not be liable for loss or damages of any kind (whether due to negligence or otherwise) arising in relation to the Equipment, its connection to the Airwave Network and/or your reliance on the content of this Connection Certificate.



Issued by: Jayesh Patel.
Head Of Airwave Ref Sys
Email: Jayesh.patel@airwavesolutions.co.uk

Date : 21st September 2010