

Network Connection Concession Certificate For Cyfas Systems C30 Radio Connected Dispatcher for use with Sepura SRM/SRG3500 v 10.5 and Motorola MTM800E v 5.13.1 Tetra Terminals

The following equipment has been tested for connection to the Airwave network (the "Equipment"). The Equipment has been tested on the Airwave Reference System Rugby.

	Manufacturer/Customer:	Versions:	Other relevant details:	Date(s) Certificate issued:
Supplier and Equipment Information	Cyfas Systems Unit 5 Ivel road Business Park 1 Ivel Road Shefford Bedfordshire SG17 5JU	Product Designation:- C30 SCR 26/1001/5 Iss 6 Operatin System:- MS Windows XP SP3 Build versions:- Sepura PEI 26/1009/2 Issue 6 C30 26/1001/5 issue 6 Motorola PEI 26/1011/1 Issue 0 Access terminal:- Sepura SRM/SRG3500 v 10.5 Motorola MTM800E v 5.13.1	Test Date: Concession by Document Inspection 26 April 12	Issued: 26 April 12

At the time the Equipment was tested the Airwave Network Reference System was configured as follows:

Airwave interface Software version	Airwave System was built to baseline	
Centracom Q303	R7.1.1 SPU	

The concession review conducted on the Equipment suggests that it will not adversely impact the Airwave Network (as it had been configured in accordance with the above specifications). The concession was limited to terminal/system conformance in accordance with the latest specification and

Updateted Date : 14 June 2012

hence no specific data application functionality or performance of the product was exercised unless specified below or in the test results..

- This certificate applies only to a C30 radio connected dispatch solution where it is connected directly through PEI to a Sepura SRM/SRG3500 mobile terminal operating with version 10.5 software.
- 2. This concession has also been extended to cover connected to Motorola MTM800E terminal version 5.13.1 based on confirmation from Cyfas of the software driver being identical as that tested on CSoft Plus product in Dec 11.
- 3. If the originating radio terminal is configured to deliver status messages in time stamped SDS format then both status and emergency indications are delivered to the operator.
- 4. The C30 PEI connected solution is not a fully integrated ICCS, and therefore has limited functionality. It does not support Ambience Listening or Patching. If multiple PEI connected fixed mobiles are available then Multiselect is supported.
- 5. The concession review has been based on release notes and information provided by Cyfas on 23 April 12.

Disclaimer:

1. This conformance certificate does not indicate any security approval with respects to the operation of this hardware / software on the Airwave network.

It is the responsibility of the supplier and their customer (whether Airwave Solutions Ltd or 3rd party customer) to ensure the Airwave Accreditor's security requirements have been met before this hardware / software is deployed on the Airwave operational network. If this solution is deployed within the customer's security domain then the customers Accreditor / Senior officer responsible for security must give their approval inline with the Airwave Service Code of Connection.

2. The issuing of this Connection Certificate is for information purposes only and Airwave makes no warranty or guarantee whatsoever as to the fitness for purpose of the Equipment or its ability to operate correctly when connected to the Airwave Network or any other network or equipment. Your use of the Equipment, connection of the Equipment to the Airwave Network and reliance on the contents of this Connection Certificate (for whatever purpose) is at your sole risk. Airwave shall not be liable for loss or damages of any kind (whether due to negligence or otherwise) arising in relation to the Equipment, its connection to the Airwave Network and/or your reliance on the content of this Connection Certificate.

Issued by: Jayesh Patel. Head Of Airwave Ref Sys Email: <u>Jayesh.patel@airwavesolutions.co.uk</u>

Updateted Date : 14 June 2012